

# POWER REGULATOR

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates to a power regulator, and more specifically to a power regulator that is upright and has a fuse so a power control box using the power regulator requires less space.

### 2. Description of Related Art

A power control box is usually used in electrical equipment and has numerous devices such as a main controller, a circuit breaker, a power controller, relays, a fuse, a power regulator, etc.

When power regulators operate, heat is produced so power regulators usually have a heat sink.

With reference to Figs. 6 and 7, conventional power regulators (60, 60') are directly connected to or mounted on a heat sink (70, 70'). When a conventional power regulator (60') is directly mounted on a heat sink (70'), the power regulator (60') is composed of a casing (61) and a printed circuit board (PCB) (62). The PCB (62) is mounted horizontally in the casing (61) and has a power transistor (621). The power transistor (621) produces very much heat, so the power transistor (621) has a heat-conduction plate (622). The heat-conduction plate (622) is attached to the casing (61) and the heat sink (70') by a screw (623). Consequently, the heat from the power transistor (622) can pass to the heat sink (70') through the heat-conduction plate (622) and the screw (623).

Most electrical devices do not use the same size power control box, and the power control box in newer electrical equipment trends to be smaller than

1 the power control box in older electrical equipment. Therefore, reducing the  
2 footprint of the power control box is not only desirable for newer electrical  
3 equipment but is an absolute necessity in many cases. However, the PCB  
4 mounted horizontally in the casing of a conventional power regulator is a  
5 minimum limitation to the size of the footprint of the power control box.

6 The present invention provides a narrower power regulator to mitigate  
7 or obviate the aforementioned problems.

#### 8 SUMMARY OF THE INVENTION

9 An objective of the present invention is to provide a power regulator  
10 that has a narrow footprint.

11 Another objective of the present invention is to provide an internal fuse  
12 so the power control box does not have to have an external fuse.

13 Other objectives, advantages and novel features of the invention will  
14 become more apparent from the following detailed description when taken in  
15 conjunction with the accompanying drawings.

#### 16 BRIEF DESCRIPTION OF THE DRAWINGS

17 Fig. 1 is a perspective view of a power regulator in accordance with the  
18 present invention;

19 Fig. 2 is an exploded perspective view of the power regulator in Fig. 1;

20 Fig. 3 is a cross sectional right side plan view of the power regulator in  
21 Fig. 1;

22 Fig. 4 is an operational perspective view of the power regulator in Fig.  
23 1 with the fuse being removed;

24 Fig. 5 is an operational perspective view of the power regulator in Fig.

1 with a wire being connected;

Fig. 6 is a perspective view of a conventional power regulator in accordance with the prior art; and

Fig. 7 is an exploded perspective view of another embodiment of a conventional power regulator in accordance with the prior art.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference to Figs. 1 and 2, a power regulator in accordance with the present invention includes a heat sink (10), a case (30) and a printed circuit board (PCB) (20).

The heat sink (10) is an upright rectangular cuboid and has a top (101), a longitudinal central wall (not numbered), multiple fins (not numbered) and a bottom (not numbered). The top (101) is rectangular and has a front edge (not numbered), a rear edge (not numbered), a left side edge (not numbered), a right side edge (not numbered), a top surface (not numbered) and a bottom (not numbered). The top surface has a longitudinal PCB slot (11), a longitudinal recess (not numbered) and at least one threaded hole (12). The left and right side edges have at least one connector element (not numbered) in each edge. The connector elements may be threaded holes (not numbered), protruding ridges (not shown), protruding lips (not shown), detents (not shown) or the like.

The case (30) has a top face (301), a front face (304), a rear face (not shown), a right side (302), a left side (303), an open bottom (not numbered), a fuse access hole (34), a wire connector access hole (35), a case connector element (not numbered) and an inside chamber (not numbered) and is mounted on the top (101) of the heat sink (10).

1           The top face (301) is rectangular and has a front edge (not numbered),  
2   a rear edge (not numbered), a left side edge (not numbered), a right side edge  
3   (not numbered), indicating holes (37) and two terminal access holes (36). The  
4   terminal access holes (36) are formed near the rear edge and respectively near  
5   the left and right side edges.

6           The front face (304) is rectangular and has a top edge (not numbered),  
7   a left edge (not numbered), a right edge (not numbered) and a bottom edge (not  
8   numbered). The top edge of the front face (304) is integrally formed with the  
9   front edge of the top face (301).

10          The fuse access hole (34) is formed through the front face (304) and the  
11   top face (301) and has a top recess (341). The fuse access hole (34) is formed  
12   between the terminal access holes (36) toward the left side edges of the top face  
13   (304) and the front face (301). The top recess (341) can be a rectangular shape  
14   or a circular shape.

15          The wire connector access hole (35) is formed through the front face  
16   (304) and the top face (301) between the terminal access holes (36) toward the  
17   right side edges of the top face (304) and the front face (301).

18          The rear face is rectangular and has a top edge (not shown), a left side  
19   edge (not shown), a right side edge (not shown) and a bottom edge (not shown)  
20   The top edge is integrally formed with the rear edge of the top face (301).

21          The right side (302) and the left side (303) are slightly trapezoidal or  
22   rectangular, are elongated vertically and are mirror images of each other. Each  
23   side (302, 303) has a top edge (not numbered), a bottom edge (not numbered), a  
24   front edge (not numbered), a rear edge (not numbered), multiple heat-

1 dissipating holes (32), at least one wire hole (33), an outside surface (not  
2 numbered), an inside surface (not numbered) and a vertical PCB slot (31). The  
3 wire hole (33) is formed near the rear edge and toward the top edge. The inside  
4 surface has a shoulder (not numbered). The shoulder is formed near the bottom  
5 edge and corresponds to the left or right end of the top of the heat sink (10).  
6 The vertical PCB slots (31) are formed respectively on the inside surfaces of  
7 the right and left sides (302, 303) and align with the longitudinal PCB slot (11)  
8 in the top (101) of the heat sink (10).

9         The case connector elements are formed near the bottom edges of the  
10 right and left sides (302, 303), correspond to the connector elements on the heat  
11 sink (10) and may be holes and screws, interlocking ribs, hooks, clamps or the  
12 like. The case connector elements securely attach the case (30) to the heat sink  
13 (10).

14         With further reference to Fig. 3, the PCB (20) is thin and is mounted  
15 vertically in the vertical slots (31) in the right and left sides (302, 303) of the  
16 case (30) and the longitudinal PCB slot (11) in the top (101) of the heat sink  
17 (10). Consequently, the case (30) has a narrow elongated footprint (not shown),  
18 and the heat sink (10) has a shape corresponding to the footprint of the case  
19 (30).

20         The PCB (20) has a front face (201), a top edge (202), a bottom edge  
21 (203), a left side edge (204), a right side edge (205), a circuit (not numbered), a  
22 fuse bracket (21), a power input terminal (22), a power output terminal (23) and  
23 a wire connector (24). The fuse bracket (21), the power input and output  
24 terminals (22, 23) and the wire connector (24) are mounted on the front face

1 (201) close to the top edge (202) of the PCB (20). The input and output  
2 terminals (22, 23) are respectively close to opposite side edges (204, 205),  
3 correspond to the wire holes (33) in the right and left side (302, 303) of the case  
4 (30) and align respectively with the terminal access holes (36) in the top face  
5 (301) of the case (30). The circuit formed on the front face (201) includes a  
6 transformer (25), a fuse (26), power transistors (27) and indicators (28). The  
7 fuse bracket (21) is mounted on the front face (201) and corresponds to the fuse  
8 access hole (34) in the front and top faces (304, 301) of the case (10). With  
9 further reference to Fig. 4, the fuse (26) is mounted in or removed from the fuse  
10 bracket (21) with a fuse puller (50). The power transistors (27) are mounted on  
11 the front face (201) close to the bottom edge (203) and are separated by a gap  
12 (not numbered). Each power transistor (27) has a metal heat-conduction plate  
13 (271) that faces the heat sink (10) and abut the heat sink (10) when the heat  
14 sink (10) is mounted in the PCB slots (11, 31) and the case (30) is attached to  
15 the heat sink (10). The indicators (28) are mounted on the front face (201) close  
16 to the top edge (202) and correspond to the indicator holes in the top face (301)  
17 of the case (30).

18         The power regulator can optionally include a PCB clamp (not  
19 numbered) that is composed of a clamp (41) with a through hole (401) and a  
20 screw (42). The top (101) of the heat sink (10) further has a threaded hole (12)  
21 corresponding to the gap between the two power transistors (27). The clamp  
22 (41) is placed on the two power transistors (27), and the screw (42) is passed  
23 through the through hole (401) and screwed into the threaded hole (12) in the  
24 top (11) of the heat sink. Thereby, the two power transistors (27) are securely

1 attached to the top (11) of the heat sink (10).

2 With reference to Fig. 4, the fuse (26) on the fuse bracket (21) is  
3 exposed through the fuse access hole (34) in the case (30) so the fuse (26) can  
4 be easily replaced by a fuse puller (50).

5 With further reference to Fig. 5, two power wires (51) are passed  
6 respectively through the two wire holes (33) and connected to the power input  
7 and output terminals. A person can insert a screwdriver (53) through the  
8 terminal access holes (36) and attach power wires (51) to or disconnect power  
9 wires (51) from the power input and output terminals (22, 23). The wire  
10 connector (24) is accessible through the wire connector access hole (35) in the  
11 front and top face (304, 301) of the case (30) so a person can easily connect  
12 signal wires (52) to the wire connector (24).

13 As mentioned above, the PCB (20) is mounted vertically on the heat  
14 sink (10) so the power regulator is tall and narrow. Therefore, the power  
15 regulator having the thin case and the heat sink can be mounted in a small  
16 power control box. In addition, the power regulator has a fuse bracket to hold a  
17 fuse so the power control box does not need an external fuse. That is, more  
18 space is available in the power control box. Further, the case has holes  
19 corresponding to the power input and output terminals, fuse and wire connector,  
20 etc. so a person can easily connect power wires and change the fuse without  
21 removing the PCB from the case.

22 Even though numerous characteristics and advantages of the present  
23 invention have been set forth in the foregoing description, together with details  
24 of the structure and function of the invention, the disclosure is illustrative only,

1 and changes may be made in detail, especially in matters of shape, size, and  
2 arrangement of parts within the principles of the invention to the full extent  
3 indicated by the broad general meaning of the terms in which the appended  
4 claims are expressed.